



NEW RANGE

ZODIAC® PRO OPEN



PURE ADVENTURE*

* Unique player!



Pro Open 650 NEO

The design of the new Pro Open Range is firmly focused on adventure boating, while providing a perfect balance of performance and comfort.

With excellent sea keeping qualities thanks to Zodiac®'s deep V-shaped hull and optimized deck plan, the Pro Open provides exceptional ride quality and comfort.

The Pro Open is designed in such a way that it can be easily transported, even with the buoyancy tubes inflated.

The Pro Open allows you to share your passion for boating with friends and family in style and comfort.

Your move!

The Points of the PRO OPEN

Special Technical Features

- Deep V-shaped hull
- Removable buoyancy tubes that are Zodiac® patented

On-board Comfort

- Ease of movement
- Self-draining deck
- Tilt steering console with storage area
- 54 litre cooler on the Pro Open 650
- 75 litre fuel tank (Pro Open 550) or 120 litre fuel tank (Pro Open 650)
- Navigation lights
- Bathing ladder

New Features

- Grey and orange (NEO) and grey and black (PVC) colours for the removable buoyancy tubes
- Three-place aft bench seat is standard on the Pro Open 550



Pro Open 550 NEO



Pro Open 550 NEO

The Pro Open 550 has a brandnew aft bench seat that three passengers for improved comfort when boating, whatever the sea conditions. The adjustable centre seat allows a ski mast to be installed or the engine to be folded down in flash.



Pro Open 550 NEO



Pro Open 550 NEO



Pro Open 650 NEO



PVC



NEO



NEO

	PRO OPEN 550	PRO OPEN 650
DIMENSIONS (in metres – feet/inches)		
Overall length	5,5 - 18'1"	6,5 - 21'4"
Inside length	3,35 - 10'12"	4,95 - 16'3"
Overall width	2,5 - 8'2"	2,5 - 8'2"
Inside width	1,35 - 4'5"	1,35 - 4'5"
CAPACITY		
Number of passengers (ISO Cat B/C)	11	5 / 13
Total weight (kg - lbs)	440 - 970	670 - 1477
DESIGN CATEGORY		
European Directive No. 94/25/CE	C	B / C
OUTBOARD DATA		
Shaft: ● Short ■ Long ✕ Extra long * Ultra long	■	mono ✕ bi ■
Maximum recommended power ² (in Hp - kW)	90 - 67	150 - 112 -
Maximum power allowed ³ (in Hp - kW)	120 - 90	175 - 131 2 x 80 - 2 x 59
Maximum speed ⁵ (in km/h - knots)	72 - 45	77 - 48
Hull angle	24°	24°

Indicated measurements may vary by +/- 3%, or +/- 5% for weight and speed measurements. (1) Maximum permitted load is calculated using ISO standards. Caution is advised when operating fully laden boats. (2) Recommended power is based on optimal use of the boat's abilities under average load. Depending on use, choose either maximum (waterskiing) or minimum power (fishing, cruising). (3) The manufacturer's plaque specifies maximum permitted power. The power of your boat must not exceed this under any circumstances. (4) Maximum permitted weight: dry weight, according to motor manufacturers' catalogue specifications. (5) Maximum speeds are intended as a guide only; they were measured in ideal conditions by professional pilots with one person aboard. They may vary according to make of motor, boat load, propeller type and water conditions. (6) Models in this catalogue are sometimes shown with optional accessories. Please check standard equipment supplied with each model and see your distributor for any additional equipment. The availability of certain models, as well as certain equipment details may vary from country to country (e.g. USA, Canada). The boats photographed in this catalogue may differ from the actual models. Zodiac® continually strives to improve the quality of its products and as such reserves the right to modify or delete any model presented in this catalogue without prior notice. Zodiac® recommends that a life jacket is worn at all times; it is your own responsibility to check the legal obligations on your navigation zone.

*5 year warranty on tube fabric and 2 year warranty on hull and tube assembling. Some warranty extensions are available depending on product and geographical areas. For more information please contact your local dealer or visit zodiacmarine.com

EQUIPMENT

HULL

- Deep V-shaped polyester hull
- Moulded non-slip deck
- Self-draining cockpit
- 1 bow ring
- 1 bow mooring post
- 2 stern mooring cleats
- Central hold
- Bow locker divided into two compartments:
 - Anchor locker
 - + removable storage bin
- 2 stern lockers
- 2 bailers

BUOYANCYTUBE

- Removable buoyancy tube
- Strongan™ Duotex™

- 2 x 1100 decitex fabric on the Pro Open 550 PVC model
- Hypalon™-Neoprene™ 1100 decitex fabric on the Pro Open 550 NEO and 1670 decitex fabric on the Pro Open 650 NEO
- Polyester bow roller
- "Easy Push" valves
- Lateral lifelines
- 4 external handles
- Ultra-wide anti-chafing deflector strip
- Short cones

STANDARD EQUIPMENT

- Reclining steering console cylinder with:
 - Steering wheel
 - + steering unit
 - + cable (550)
- Hydraulic steering (650)
- Pilot's and co-pilot's bolster with:
 - Footrest
 - Handrail
 - 4 fishing rod holders
 - Storage box

- Windscreen
- Stainless steel handrail
- Console doors
- Navigation lights
- Fitted fuel tank with gauge (75 litres on the Pro Open 550/ 120 litres on the Pro Open 650)
 - + water/fuel separator
- Bathing ladder
- Bilge pump
- Battery cut-off switch
- 2 paddles
- Foot pump
- 1 repair kit
- Owner's manual

EQUIPMENT SPECIFIC TO 550

- 3 aft passenger seats with adjustable centre seat

EQUIPMENT SPECIFIC TO 650

- Upholstered cooler seat (54 litres capacity)
- Aft seating with removable backrest
- Bathing ladder

OPTIONAL EQUIPMENT

- Removable backrest for bolster
- Bimini top
- Sundeck
- Ski mast
- Mooring awning

For more information, visit

www.zodiacmarine.com

Zodiac® is a registered trade mark - Copyright© Zodiac® 2013